

HG2578 Series

HG2578 series with through hole 25.4mm , OD78mm , suitable for rotating application which requires a through hole $\leq 25.4\text{mm}$

Standard model supports 1-24 power rings(0-10A/ring) or 1-48 signal rings(0~5A/ring)



Features

- ◆ Multi-point brush contact material ensure long life
- ◆ Integrated structure design for easy installation
- ◆ Standard model supports 1-24 power rings(0-10A/ring) or 1-48 signal rings(0~5A/ring)
- ◆ Both the data bus agreement compatible
- ◆ Transmit analog and digital signals
- ◆ Both the data bus agreement compatible
- ◆ Free maintenance

Typical application

- ◆ Automatic machines
- ◆ Cable reels
- ◆ Robotics, rotary sensors, urgent illumination equipment
- ◆ Exhibit / display equipment
- ◆ Packaging
- ◆ Rotary table
- ◆ Medical, Pharmaceutical equipment
- ◆ Converting machines
- ◆ Capping machines
- ◆ Labeling machines
- ◆ Filling machine
- ◆ Machine tools

Options

- ◆ Optional for underwater IP65, IP68 Operation speed, current & voltage
- ◆ No. of rings
- ◆ Connector
- ◆ Housing material
- ◆ Position of wire outlet, wire length
- ◆ Protection level (dust and water)
- ◆ Flange mounting is optional
- ◆ Operating temperature
- ◆ Support mixed high speed data transmission(including Ethernet, USB, Profibus, Ethercat, CANOPEN, CANBUS, RS232, RS485, etc.)
- ◆ Fluidic rotary joints, FORJ and electric slip ring can be mixed.


Specifications

Electrical Data			Mechanical Data	
	Power	Signal	Max. Speed	0-250 rpm
Rated Current	10A/ring	5A/ring	Working Temperature	-20°C~+80°C
Rated Voltage	0~380VAC/VDC	0~240VAC/VDC	Working Humidity	0-85% RH
Insulation Resistance	≥1000MΩ/500VDC	≥500MΩ/500VDC	Structure Material	Engineering plastic
Dielectric Strength	1000VAC@50Hz,60s	500VAC@50Hz,60s	Contact material	Precious metal
Wire Size	Sliver plated Teflon AWG16(10A)	Sliver plated Teflon AWG22(5A)	Operating Torque	0.1N·m for 6 rings, 0.03 N·m increased for every 6 rings added
Wire Length	Standard 500mm(adjustable)			
Dynamic Resistance	<0.01Ω		Protection level	IP51

Wires Color Code

Ring#	1	2	3	4	5	6	7	8	9	10	11	12
Color	RED	YEL	BLK	BLU	GRN	WHT	PUP	GRY	BRN	ORN	DBLU	KHK

Drawing for HG2578



Model List

Model	Power Ring(10A)	Signal Ring(5A)	Length L(mm)
HG2578-6P	6	-	55
HG2578-12S	-	12	55
HG2578-12P	12	-	79
HG2578-6P/12S	6	12	79
HG2578-24S	-	24	79
HG2578-18P	18	-	103
HG2578-12P/12S	12	12	103
HG2578-6P/24S	6	24	103
HG2578-36S	-	36	103
HG2578-24P	24	-	127
HG2578-18P/12S	18	12	127
HG2578-12P/24S	12	24	127
HG2578-6P/36S	6	36	127
HG2578-48S	-	48	127