

High speed rotating slip ring - SH Series

Slip rings of the SH series are specially design for high speed slip ring, precision ball bearings and the patented fiber brush design allow operation up to 15,000 rpm. Fiber brush technology offers several advantages over conventional slip ring contacts including multiple points of contact per brush bundle, low contact force per fiber and low contact wear rates.

Features

- ◆ Compact design
- ◆ No maintenance
- ◆ Operating smoothly and reliability
- ◆ Extremely low electrical noise
- ◆ Convenient to assembly
- ◆ Compatible with data bus protocols
- ◆ Precious metal contact ensures long life-span

Typical applications

- ◆ Electrical test equipment
- ◆ Indexing tables, Cable reels
- ◆ Robotics, rotary sensors, urgent illumination equipment
- ◆ Exhibit / display equipment
- ◆ CCTV pan
- ◆ Laboratory equipment

Options

- ◆ Working speed
- ◆ Rated voltage
- ◆ Rated current
- ◆ No. of rings
- ◆ Connector
- ◆ Flange mounting
- ◆ Housing material
- ◆ Position of wire outlet, wire length
- ◆ Protection level (dust and water)

Specifications for SHT033-36

Electrical Data		Mechanical Data	
No. of Rings	36rings	Outer Diameter	32.6mm
Rated Current	3A/ring	Working Speed	2000rpm
Rated Voltage	24VDC	Working Temperature	-20°C~+80°C
Dielectric Strength	300VAC@50HZ,60S	Working Humidity	60% RH or higher
Insulation Resistance	300MΩ/500VDC	Structure Material	Aluminium alloy
Electrical Noise	<0.01Ω	Contact Material	Precious metals
Lead Length	1000mm	IP Rating	IP51

Drawing for Outline Dimension

